



TECHNICAL DATA SHEET

CALCIUM RESINATE (Flammable Solid, NOS) TYPE II / PRECIPITATED

CAS # 9007-13-0 FORMULA: Not Available

FORMULA WEIGHT Variable UN # UN1313

Calcium Resinate Content	77.0% Min
Acid Number (pH)	33 Max
Chloroform –Insoluble Matter	3.0% Max
Water Content	5.0% Max
Flame Test	Yellow Red

Other grades available upon request as well as material prepared to customer and government specifications. Custom milling, blending, screening and packaging are available at a reasonable cost. All raw materials undergo testing for conformance as well as in-process sampling and final shipping samples. Barium & Chemicals, Inc. has a full-course, in-house laboratory whose staff has expertise in wet chemical analysis as well as AA, IC, ICP, W.S. Tyler Ro-Tap, Fisher Sub-Sieve Sizer, Laser Particle Analysis, pH, titration and moisture analysis.

Special requests may require extra lead time for raw material manufacture and processing. Allow sufficient time when ordering.

USES: Waterproofing, manufacturing paint driers, porcelains, perfumes, cosmetics, enamels, coating for fabrics, wood, paper, and tanning leather.

PACKAGE TYPE: Fiber, Steel or Plastic drums with polyliner.

Packaged for transport by ground, air or ocean transport. Call for packaging options.